

SSH

scissor lift for trucks and busses



IME-AUTOLIFT

Autolift GmbH

subfloor and onfloor versions



technical data

	SSH 80	SSH 100	SSH 160	SSH 200	SSH 240	SSH 300	SSH 320	SSH 400
capacity	8000 kg	10.000 kg	16.000 kg	20.000 kg	24.000 kg	30.000 kg	32.000 kg	40.000 kg
track length	6000 mm	6000 mm	8000 mm	8000 mm	11.000 mm	11.000 mm	14.000 mm	14.000 mm
ground height	350 mm	350 mm	350 mm	350 mm	350 mm	350 mm	350 mm	350 mm
lifting height	2100 mm	2100 mm	2100 mm	2100 mm	2100 mm	2100 mm	2100 mm	2100 mm
voltage	400 V, 50 Hz 2,2 kW	400 V, 50 Hz 2,2 kW	400 V, 50 Hz 2 x 2,2 kW	400 V, 50 Hz 2 x 2,2 kW	400 V, 50 Hz 3 x 2,2 kW	400 V, 50 Hz 3 x 2,2 kW	400 V, 50 Hz 4 x 2,2 kW	400 V, 50 Hz 4 x 2,2 kW
	1 pair of scissor 4 synchronised lifting cylinders	1 pair of scissor 4 synchronised lifting cylinders	2 pair of scissors 8 synchronised lifting cylinders	2 pair of scissors 8 synchronised lifting cylinders	3 pair of scissors 12 synchronised lifting cylinders	3 pair of scissors 12 synchronised lifting cylinders	4 pair of scissors 16 synchronised lifting cylinders	4 pair of scissors 16 synchronised lifting cylinders



IME-AUTOLIFT

Autolift GmbH

SSH – scissor lift for trucks and busses

- no connecting bars between the tracks, no mechanical connection between the both sides, gives possibility for variable space between the tracks, free passing between the tracks
- hydraulic synchronization with double, in opposite direction working differential-cylinder system, no electrical or electronic parts on the scissors necessary
- Safety descending system with acoustic signal, descending possibility per hand
- Rolling up security plates on both ends of the tracks



SSH-types

SSH 80, SSH 100



SSH 160, SSH 200



SSH 240, SSH 300



SSH 320, SSH 400



Autolift GmbH

Mayrwiesstraße 16
5300 Hallwang/Salzburg
Tel.: +43 662 - 45 05 88
Fax: +43 662 - 45 05 88 - 18
Mail: office@autolift.info
Web: www.autolift.info

delivery standard

- Scissor lift with hydraulic lifting cylinders and tracks
- Hydraulic power unit inside the control desk
- Descending possibility per hand
- Connection hoses between scissors and from scissors to the control desk

options

- Drive on ramps (2 pieces)
- Axle free lifter 10 t capacity, 300 mm stroke